

arno fuchs kabeltechnik



RotaryStrip 2400 Stripping Machine

- Intuitive color touchscreen user interface
- Networking capability
- LED lighting provides the operator with a clear view of the entire working area
- Very sensitive trigger sensor. Works great for small, flexible wires
- No mechanical adjustments required when changing wire sizes
- Controlled twisting of inner conductor strands
- Barcode scanning function

RotaryStrip 2400

Application Range | Function

The Schleuniger RotaryStrip 2400 strips wires ranging in size from 0.013 – 6 mm² (36 – 10 AWG) and jacketed cables up to 7 mm (0.27") in diameter. The main applications are difficult to process insulations and wires where a controlled twisting of the inner conductors is required. This innovative machine does not require any mechanical adjustments to process different wire sizes. Using the color touch-screen, the operator selects the desired wire size from the preprogrammed library and all parameters (incision diameter, clamping pressure, blade way back, etc.) are automatically set.

The operator edits the stripping and pull-off lengths as required and the machine is ready for operation.

The RotaryStrip 2400 begins the stripping process when the wire end touches the trigger sensor. The wire is automatically clamped and the stripping process is performed according to the programmed values. If desired, the program can be saved to internal memory for future use.

Programmable Processing Parameters

- Rotary Speed
- Incision diameter, incision speed, incision time
- Blade way back
(default values in "Basic Wire", programmable in "Extended Wire")
- Stripping length, pull-off length, pull-off speed
- Cable clamping pressure
- Twisting force / twisting direction

Technical specifications	
Conductor Cross-Section	0.013 – 6 mm ² (36 – 10 AWG)
Raw Material Diameter	Maximum 7 mm (0.27")
Diameter Increments	0.01 mm (0.001")
Strip Length	Minimum 0.1 mm (0.01") Maximum 34 mm (1.33")
Strip Length Increments	0.1 mm (0.01")
Twisting Range	0.14 - 2.50 mm ² (26 - 13 AWG)
Cycle Time	1 s (0.75 mm ² (18 AWG) wire, stripping length 10 mm (0.39"), pull-off length 5 mm(0.19"))
Cycle Start	Automatic trigger sensor or optional foot pedal
Available Stripping Blades	Flat-blades (carbide)
Raw Material Type	PVC, PUR, rubber, Teflon®, Tefzel®, Kapton, etc.
Clamping	Programmable clamping force
Memory Capacity	1000 wires or cables (memory function only with "Extended Wire")
Interfaces	Foot pedal, USB "Host"
Options	Foot pedal, radius centralizers
Noise Level	< 70 db (A)
Power Supply	100/115 VAC, 230/240 VAC, 100 VA, 50/60 Hz
Dimension (L x W x H)	390 x 130 x 280 mm (15.3 x 5.1 x 11.0")
Weight	10 kg (22 lbs.)
CE-Conformity	The RotaryStrip 2400 fully complies with all CE and EMC equipment guidelines relative to mechanical and electrical safety and electromagnetic compatibility.
Important Note	Schleuniger recommends that wire samples be submitted in case where there is doubt as to the processing capabilities of a particular machine.

Hausanschrift: Arno Fuchs GmbH
Oberwiesenweg 24
D-73734 Esslingen

Internet: www.arnofuchs.de
info@arnofuchs.de

Telefon: *49(0)711-9199170

Telefax: *49(0)711-9199179

arno fuchs
kabeltechnik